

GS-10/20/30 Orbital Shaker

GS-10/20/30 orbital shaker is compact and amazingly designed. It is used for any mixing applications in different industries. Built with DC brushless motor, adopted micro-computer control technology, the orbital shaker is easy to operate. Gentle shaking, it is applied in different laboratories of molecular biology, microbiology, immunology, chemistry, etc.



Speed Range



3 Shaking Orbit
optional



Time Setting



6 Platforms



【 Product Features 】

1. DC brushless motor, safe, long life and free of maintenance. Operating silent and stable.
2. Speed adjustable. Gentle shaking, applied in different industries.
3. Compact and clean designed, LED display time and speed, streamlined fuselage, simple operation, convenient for cleaning.
4. Timing function. Beep alarm when operation ends.
5. Different platforms to adapt different conical flasks and other sample containers for optional choices.



Platform PP-4



Double-level platform PP-4A



PW-260 Universal platform



UP-12 Adjustable Universal
Platform

【 Technical Parameters 】

Model	GS-10	GS-20	GS-30
Speed Range	50rpm ~350rpm	50rpm ~300rpm	50rpm ~250rpm
Shaking Orbit	10mm	20mm	30mm
Time Range	1min ~99h59min or continuous	1min ~99h59min or continuous	1min ~99h59min or continuous
Max. Load	2.5kgs	2.5kgs	2.0kgs
Voltage	AC 100 ~230V, 50/60Hz	AC 100 ~230V, 50/60Hz	AC 100 ~230V, 50/60Hz
Power	50W	50W	50W
Fuse	250V, 1A, Φ 5x20	250V, 1A, Φ 5x20	250V, 1A, Φ 5x20
Dimension (WxDxH)	284 x 264 x 108mm	284 x 264 x 108mm	284 x 264 x 108mm
Net Weight	5.6kgs	5.6kgs	5.6kgs



P6-250 Conical Flask
Stand



P12-100 Conical Flask
Stand