

Price for Andbon Dry Cabinet (2021.1.11)

Page 2 of 5

Product Model	AD-30S	AD-50S	AD-70S	AD-80S	AD-90S	AD-100S	AD-160S	AD-180S
Product View								
Capacity (L)	30	50	70	80	90	100	160	180
input voltage	110-220V AC/ 5V 2A DC						110-220V AC/ 5V 5A DC	
Power	<8W						<15W	
control number (PC)	1						2	
humidity control mode	Automation control							
dehumidity range	25%-60%							
disply mode	LED display							
shelf material and number	plastic / 1PC	plastic / 2PCS		plastic / 3PCS		plastic / 4PCS	plastic / 5PCS	
adjustable foot number	without	2pcs smaller					2pcs bigger	
inner size W*D*H(mm)	288*290*365	288*290*530	378*360*477	378*360*543	378*360*607	378*358*690	UP:378*360*477 DOWN:378*360*607	Up:378*360*543 Down: 378*360*690
out sizeW*D*H(mm)	290*320*420	290*320*605	380*390*550	380*390*616	380*390*680	380*390*770	380*390*1180	380*390*1345
packing carton size W*D*H(mm)	350*380*485	385*350*670	440*450*610	440*450*680	440*450*740	440*450*835	440*450*1245	440*450*1400
N.G.: (kg)	6.5	9.1	11.65	12.35	13.95	13.86	23.65	26.5
G.W.: (kg)	7.6	10.8	13.55	14.9	16.2	16.36	26.85	30

Price for Andbon Dry Cabinet (2021.1.11)

Page 3 of 5

Product Model	AD-80HS	DS-230S	AD-250S	AD-300S	DS-500S	AD-550S	AD-600S	
Product View								
Capacity (L)	80	230	235	300	500	550	580	
input voltage	110-220V AC/ 5V 2A DC	110-220V AC / 5V 5A DC					110-220V AC/ 5V 12A DC	
Power	<8W	<15W			<50W	<15W	30W/H	
controler number (PC)	1	2			6	3	4	
humidity control mode	Automation control							
dehumidity range	25%-60%							
disply mode	LED disply							
shelf material and number	steel / 1PC	steel / 2PC	steel / 3PC				steel / 4PCS	
adjustable foot number	2	2	2	4 wheels	4 wheels	4 wheels	2	
inner size W*D*H(mm)	378*360*690	599*479*790	808*340*790	848*400*892	600*530*177	998*480*1084	849*428*1673	
out sizeW*D*H(mm)	380*390*770	600*482*852	810*370*865	850*430*965	650*580*183	1000*510*1157	851*430*1830	
packing carton size W*D*H(mm)	440*450*835	670*550*928	875*445*975	910*500*1025	660*590*1830 700*650*1890	1060*580*1265	930*470*1930	
N.G.: (kg)	13.86	27	28.75	40	57	60.8	38.75	
G.W.: (kg)	16.36	30.5	30.5	43.75	64.3KG/77.5KG	66.5	40.5	

Product Model	DS-35S	DS-55S	DS-105S	DS-125S	DS-155S	DS-195S		
Product View								
Capacity (L)	35	55	105	125	155	195		
input voltage	110-220V AC/ 5V 2A DC					110-220V AC/ 5V 5A DC		
Power	<8W				<15W			
controler number (PC)	1				2			
humidity control mode	Automation control							
dehumidity range	25%-60%							
disply mode	LED disply							
shelf material and number	plastic / 1PC	plastic / 3PCS	plastic / 3PCS	plastic / 4PCS	plastic / 4PCS	plastic / 5PCS		
adjustable foot number	2pcs bigger							
inner size W*D*H(mm)	313*290*380	313*290*580	408*388*690	408*388*817	408*388*940	up :408*388*543 down:408*388*690		
out sizeW*D*H(mm)	315*320*435	315*320*626	410*390*770	410*390*900	410*390*1015	410*390*1345		
packing carton size W*D*H(mm)	380*375*495	380*375*685	470*450*835	470*450*955	470*450*1075	470*450*1400		
N.G.: (kg)	7.1	10.1	14.6	19.2	22.75	27.8		
G.W.: (kg)	8.4	11.6	17.5	21.6	25.5	31.6		

Product View								
Capacity (L)	9L	9L	/	/				
input voltage	/	/	/	/	110-220V AC/ 5V 2A DC	110-220V AC/ 5V 2A DC		
Power	/	/	/	/	<10W	<10W		
controler number (PC)	/	/	/	/	/	/		
humidity control mode	/	/	/	/	/	/		
dehumidity range	/	/	/	/				
disply mode	/	/	/	/				
shelf material and number	/	/	/	/				
adjustable foot number	/	/	/	/				
inner size W*D*H(mm)	/	/	/	/				
out sizeW*D*H(mm)	290*230*215	/	/	/	165*82*40	165*82*40		
packing carton size W*D*H(mm)	295*238*224	/	/	/	168*88*92	213*95*92		
N.G.: (kg)	1.35	/	/	/	0.39	0.69		
G.W.: (kg)	1.75	/	/	/	0.53	0.83		